

LANIER

 **Print Page**  **Close Window**



	SP C222DN	SP C220N	SP C221N
Output Speed(LTR)	21ppm (color/b&w)	16ppm (color/b&w)	21ppm (color/b&w)
CPU Speed	300 MHz	192 MHz	300 MHz
Standard Memory	128 MB std./ 640 MB RAM max.	64 MB (Std./Max.)	128 MB std./ 640 MB RAM max.
Standard Interfaces	USB 2.0, Ethernet 10/100Base-TX, USB Host I/F for Camera Direct Printing	2.0, Ethernet 10/100Base-TX	2.0, Ethernet 10/100Base-TX
Optional Connectivity	IEEE 802.11b/g Wireless Bridge SX 2500CG	IEEE 802.11b/g Wireless Bridge SX 2500CG	IEEE 802.11b/g Wireless Bridge SX 2500CG
Languages/PDL Support	PCL5c/6, PostScript 3 emulation	DDST	PCL5c/6, PostScript 3 emulation
Duplexing	Standard	N/A	N/A
Networking	Yes	No	No
Standard Paper Supply	250-Sheet Standard Paper Tray 500-Sheet Paper Feed Unit 100-Sheet Multi-Bypass Tray	250-Sheet Standard Paper Tray 500-Sheet Paper Feed Unit 100-Sheet Multi-Bypass Tray	250-Sheet Standard Paper Tray 500-Sheet Paper Feed Unit 100-Sheet Multi-Bypass Tray
Optional Paper Supply	500 Sheet Paper Feed Unit	N/A	500 Sheet Paper Feed Unit

 **Print Page**  **Close Window**

Copyright 2001-2008 Lanier Corporation