



Print Page **Close Window**



	GX 3050SFN	GX 3000SF	GX 3000S
CPU Speed	<input type="checkbox"/> 400 MHz	<input type="checkbox"/> 400 MHz	<input type="checkbox"/> 400 MHz
Standard Memory	<input type="checkbox"/> 96 MB (Std./Max.)	<input type="checkbox"/> 96 MB (Std./Max.)	<input type="checkbox"/> 32 MB (Std./Max.)
Standard Interfaces	<input type="checkbox"/> USB 1.1/2.0, Ethernet 10/100Base-TX	<input type="checkbox"/> USB 1.1/2.0	<input type="checkbox"/> USB 1.1/2.0
Optional Connectivity	<input type="checkbox"/>	<input type="checkbox"/> Ethernet 10/100Base-TX	<input type="checkbox"/> Ethernet 10/100Base-TX
Languages	<input type="checkbox"/> RPCS, PCL5/6 and MAC	<input type="checkbox"/> RPCS and MAC	<input type="checkbox"/> RPCS and MAC
Duplexing	<input type="checkbox"/> Standard	<input type="checkbox"/> Standard	<input type="checkbox"/> Standard
Facsimile	Yes	Yes	No
Networking	Yes	No	No
Standard Paper Supply	250-Sheet Standard Paper Tray	250-Sheet Standard Paper Tray	250-Sheet Standard Paper Tray
	<input type="checkbox"/> 500-Sheet Paper Feed Unit	<input type="checkbox"/> 500-Sheet Paper Feed Unit	<input type="checkbox"/> 500-Sheet Paper Feed Unit
	100-Sheet Multi-Bypass Tray	100-Sheet Multi-Bypass Tray	100-Sheet Multi-Bypass Tray

Print Page **Close Window**

Copyright 2001-2009 Lanier Corporation