

# LANIER

 **Print Page**  **Close Window**



## LD525C

## LD525Cspf

<b>Copier Capability</b>	Standard	Standard
<b>Printing Capability</b>	Standard	Standard
<b>Scan Capability</b>	Standard	Standard
<b>Fax Capability</b>	Optional	Standard
<b>Standard Paper Supply</b>	Standard: 2 x 250 sheets + 100-Sheet Bypass Tray Maximum: 1,600 sheets	Standard: 2 x 250 sheets + 100-Sheet Bypass Tray Maximum: 1,600 sheets
<b>LAN Fax</b>	Optional	Standard
<b>Duplex</b>	Standard	Standard
<b>Connectivity</b>	10Base-T/100Base-TX Ethernet (RJ-45), USB 2.0 Device, USB 2.0 Host I/F Optional Interfaces IEEE 802.11a/b/g Interface Unit Type J, Bluetooth Interface Unit Type 3245, IEEE 1284 Interface Board Type A, Gigabit Ethernet Type A	10Base-T/100Base-TX Ethernet (RJ-45), USB 2.0 Device, USB 2.0 Host I/F Optional Interfaces IEEE 802.11a/b/g Interface Unit Type J, Bluetooth Interface Unit Type 3245, IEEE 1284 Interface Board Type A, Gigabit Ethernet Type A
<b>HDD</b>	60 GB HDD Standard (Shared)	60 GB HDD Standard (Shared)
<b>Standard Page Description Language</b>	PCL5c, PCL6, XPS, RPCS (Standard) Genuine Adobe® PostScript®3™, Includes PDF Direct Print & Mobile Printing (Optional)	PCL5c, PCL6, XPS, RPCS (Standard) Genuine Adobe® PostScript®3™, Includes PDF Direct Print & Mobile Printing (Optional)
<b>RAM</b>	768 MB (512 MB + 256 MB) RAM (Standard); 1GB RAM (Maximum)	768 MB (512 MB + 256 MB) RAM (Standard); 1GB RAM (Maximum)
<b>Scan - to Modes Supported</b>	Scan-to-Email (with LDAP support); Scan-to-Folder (SMB/FTP/NCP); Scan-to-URL; Network TWAIN scanning; Scan-to-Media (USB/SD, optional); WSD scanner (for Vista)	Scan-to-Email (with LDAP support); Scan-to-Folder (SMB/FTP/NCP); Scan-to-URL; Network TWAIN scanning; Scan-to-Media (USB/SD, optional); WSD scanner (for Vista)

 **Print Page**  **Close Window**

Copyright © 2001-2008 Lanier Corporation