



Print Page **Close Window**



	SP C222DN	SP C220N	SP C221N
Output Speed(LTR)	<input type="checkbox"/> 21ppm (color/b&w)	<input type="checkbox"/> 16ppm (color/b&w)	<input type="checkbox"/> 21ppm (color/b&w)
CPU Speed	<input type="checkbox"/> 300 MHz	<input type="checkbox"/> 192 MHz	<input type="checkbox"/> 300 MHz
Standard Memory	<input type="checkbox"/> 128 MB std./ 640 MB RAM max.	<input type="checkbox"/> 64 MB (Std./Max.)	<input type="checkbox"/> 128 MB std./ 640 MB RAM max.
Standard Interfaces	USB 2.0, Ethernet <input type="checkbox"/> 10/100Base-TX, USB Host I/F for Camera Direct Printing	2.0, Ethernet <input type="checkbox"/> 10/100Base-TX	2.0, Ethernet <input type="checkbox"/> 10/100Base-TX
Optional Connectivity	<input type="checkbox"/> IEEE 802.11b/g Wireless Bridge SX 2500CG	<input type="checkbox"/> IEEE 802.11b/g Wireless Bridge SX 2500CG	<input type="checkbox"/> IEEE 802.11b/g Wireless Bridge SX 2500CG
Languages/PDL Support	<input type="checkbox"/> PCL5c/6, PostScript 3 emulation	<input type="checkbox"/> DDST	<input type="checkbox"/> PCL5c/6, PostScript 3 emulation
Duplexing	<input type="checkbox"/> Standard	<input type="checkbox"/> N/A	<input type="checkbox"/> N/A
Networking	Yes	No	No
Standard Paper Supply	250-Sheet Standard Paper Tray <input type="checkbox"/> 500-Sheet Paper Feed Unit 100-Sheet Multi-Bypass Tray	250-Sheet Standard Paper Tray <input type="checkbox"/> 500-Sheet Paper Feed Unit 100-Sheet Multi-Bypass Tray	250-Sheet Standard Paper Tray <input type="checkbox"/> 500-Sheet Paper Feed Unit 100-Sheet Multi-Bypass Tray
Optional Paper Supply	<input type="checkbox"/> 500 Sheet Paper Feed Unit	<input type="checkbox"/> N/A	<input type="checkbox"/> 500 Sheet Paper Feed Unit

Print Page **Close Window**

Copyright 2001-2009 Lanier Corporation